

DATA SHEET

Horseshoe shim pads

Material:

 Polyethylen (PE), recycled

 PVC-, CFC- and HFC-free



Product information :

 A pressure-resistant mounting aid for use when installing precast concrete elements between protruding reinforcing bars. Not suitable for permanent fixing. Dimensions approx. 70 x 70 mm, slot approx. 22 mm wide and 45 mm deep.

 Further dimensions and solid versions without recesses on one side, from a height of 10 mm, available on request.

 Packaging units and dimensions available:

ITEM NUMBER	HEIGHT Dimension in mm	BAG PU in piece	PALLET PU in piece
397.002	2	4 x 250 (1.000)	40.000
397.003	3	4 x 250 (1.000)	40.000
397.004	4	4 x 125 (500)	20.000
397.005	5	4 x 125 (500)	20.000
397.006	6	4 x 125 (500)	20.000
397.007	7	4 x 125 (500)	20.000
397.008	8	2 x 125 (250)	10.000
397.009	9	2 x 125 (250)	10.000
397.010	10	2 x 125 (250)	10.000
397.012	12	4 x 50 (200)	8.000
397.015	15	4 x 50 (200)	8.000
397.020	20	3 x 50 (150)	6.000
397.025	25	100	4.000
397.030	30	100	4.000

Note:

This data sheet contains basic information about our products.
Its contents have been compiled with the utmost care and are continually updated.
We therefore reserve the right to make changes of any kind.
Please do not hesitate to contact us personally for further information.

Version 08/2026

