

DATA SHEET



Steckfix

Material:

RÜDE Polyolefine (PO), recycled

RÜDE PVC-, CFC- and HFC-free

Product information:

RÜDE Flexible PVC-free plastic spacer with very good concrete flow and punctiform point of contact for main use in precast manufacture by using of mesh reinforcement.

RÜDE Can be plugged in and divided into 50 or 100 cm grids. Deliverable in lengths of 100, 200 or 250 cm. Tested according to DBV-bulletin „Abstandhalter“ – Eurocode 2, version November 2019.

RÜDE Packaging units and dimensions available:

ITEM NUMBER	CONCRETE COVER dimension in mm	BUNDLE pu in m	PALLET pu in piece
Length 1,00 m			
350.015100	15	50	6.000
350.020100	20	50	4.800
350.025100	25	50	4.200
350.030100	30	50	3.600
350.035100	35	50	3.000
350.040100	40	40	2.400
350.045100	45	40	2.400
350.050100	50	40	1.920
350.060100	60	30	1.800
Length 2,00 m			
350.015	15	100	6.000
350.020	20	100	4.800
350.025	25	100	4.200
350.030	30	100	3.600
350.035	35	100	3.000
350.040	40	80	2.400
350.045	45	80	2.400
350.050	50	80	1.920
350.060	60	60	1.800
Length 2,50 m			
350.015250	15	100	9.100
350.020250	20	100	6.300
350.025250	25	100	5.600
350.030250	30	100	4.900
350.035250	35	100	4.200
350.040250	40	100	3.000
350.045250	45	100	3.000
350.050250	50	100	2.400
350.060250	60	75	2.250

Note:

This data sheet contains basic information about our products.
Its contents have been compiled with the utmost care and are continually updated.
We therefore reserve the right to make changes of any kind.
Please do not hesitate to contact us personally for further information.

Version 08/2024



RÜDE GRUPPE
D-79725 Laufenburg



+497763/92795-50



vertrieb@ruede.de

