

DATA SHEET



Steckfix base spacer with nubs

Material:



Polyethylen (PE), recycled



PVC-, CFC- and HFC-free

Product information:



Flexible PVC-free plastic spacer with very good concrete flow and punctiform contact area for main use in precast manufacture by using of rod spacers.
Little stoppers on the top avoid the moving of the rebar while concreting, the using of wire is not necessary. Deliverable in lengths of 100, 200 and 250 cm. Other lengths on request



Tested according to DBV data sheet "Abstandhalter" – Eurocode 2, version November 2019.



Packaging units and dimensions available:

ITEM NUMBER	CONCRETE COVER dimension in mm	BUNDLE pu in m	PALLET pu in m
Length 1,00 m			
351.15100	15	50	6.000
351.20100	20	50	4.800
351.25100	25	50	4.200
351.30100	30	50	3.600
351.35100	35	40	2.880
351.40100	40	40	2.400
351.45100	45	30	1.800
351.50100	50	30	1.800
Length 2,00 m			
351.15	15	100	6.000
351.20	20	100	4.800
351.25	25	100	4.200
351.30	30	100	3.600
351.35	35	80	2.880
351.40	40	80	2.400
351.45	45	60	1.800
351.50	50	60	1.800
Length 2,50 m			
351.15250	15	100	7.700
351.20250	20	100	6.300
351.25250	25	100	5.600
351.30250	30	100	4.900
351.35250	35	100	4.200
351.40250	40	100	3.000
351.45250	45	75	2.250
351.50250	50	75	2.250

Note:

This data sheet contains basic information about our products.
Its contents have been compiled with the utmost care and are continually updated.
We therefore reserve the right to make changes of any kind.
Please do not hesitate to contact us personally for further information.

Version 08/2024

