

DATA SHEET



SP-Fix

Material:



Polyolefine (PO), recycled



PVC-, CFC- and HFC-free



Product information :



Slightly wavelike PVC-free spacer with a very good concrete flow for use in precast work. Tilt proof due to a width of 45 mm.



Less and small contact points on the formwork give slight visible imprints on the precast concrete element.



If required, endless extension through plug-in connection. The form of the spacer guarantees an efficient packaging without distortion.



Tested according to DBV data sheet "Abstandhalter" – Eurocode 2, version November 2019.



Packaging units and dimensions available:

ITEM NUMBER	CONCRETE COVER dimension in mm	BUNDLE pu in m	PALLET pu in m
Length 118 cm			
352.015	15	88,5	4.956
352.020	20	88,5	4.956
352.025	25	88,5	4.956
352.030	30	88,5	4.336
352.035	35	88,5	3.186
Length 236 cm			
352.015l	15	118	9.440
352.020l	20	118	9.440
352.025l	25	118	9.440
352.030l	30	118	7.434
352.035l	35	118	6.608

Note:

This data sheet contains basic information about our products.
Its contents have been compiled with the utmost care and are continually updated.
We therefore reserve the right to make changes of any kind.
Please do not hesitate to contact us personally for further information.

Version 08/2024

