

DATA SHEET

Raster-Fix

Material:



Polyolefine (PO), recycled



PVC-, CFC- and HFC-free

Product information:



Stable track spacer in wave-shaped construction with good concrete flow for supporting horizontal reinforcement. Due to the large recesses and offset contact surface on the formwork, there is no linear concrete breakthrough in the concrete.



At the same time, the formation of air pockets (cavities) is minimized even when using coarse-grained concrete.



Installation as short piece or endless extension through plug connector. Endless installation in a zigzag shape possible with the aid of the ring mount at the plug connection.



Tested according to DBV data sheet "Abstandhalter" – Eurocode 2, version November 2019.



Packaging units and dimensions available:

ITEM NUMBER	CONCRETE COVER Dimension in mm	BUNDLE PU in m	PALLET PU in m
LENGTH 2,00 M			
355.25	25	100	3.600
355.30	30	100	3.000
355.35	35	80	2.400
355.40	40	80	2.400
LENGTH 0,67 M			
	Dimension in mm	PU in piece	PU in piece
355.ST25	25	50	2.100
355.ST30	30	50	1.750
355.ST35	35	40	1.400
355.ST40	40	40	1.400

Note:

This data sheet contains basic information about our products.
Its contents have been compiled with the utmost care and are continually updated.
We therefore reserve the right to make changes of any kind.
Please do not hesitate to contact us personally for further information.

Version 09/2024

