

DATA SHEET

ISI-rocket for precast walls

Material:



Steel (ST), Polypropylen (PP)



PVC-, CFC- and HFC-free



Product information :



Spacer for the double wall production of 8 mm steel with injection-moulded head and foot. By the injection of head and foot, we reach minimal differences in the lengths of individual rockets which guarantees accurate walls during concreting.



Contact area for 15-, 20-, 25- and 30-mm concrete cover. The ISI rockets can be extended using our extension pieces in 10-, 20-, 30- and 40-mm lengths. Please note that the WU test expires when using the extension pieces.



Tested according to DBV data sheet "Abstandhalter" – Eurocode 2, version November 2019.

ITEM NUMBER	HEIGHT Dimension in mm	BAG PU in piece	PALLET PU in piece
364.L120	120	100	5.000
364.L130	130	100	5.000
364.L140	140	100	5.000
364.L150	150	100	5.000
364.L160	160	100	5.000
364.L170	170	100	5.000
364.L180	180	100	5.000
364.L190	190	100	5.000
364.L200	200	100	5.000
364.L210	210	100	4.000
364.L220	220	100	4.000
364.L230	230	100	4.000
364.L240	240	100	4.000
364.L250	250	100	4.000
364.L260	260	100	4.000
364.L270	270	100	4.000
364.L280	280	100	4.000
364.L290	290	100	4.000
364.L300	300	50	3.000

Note:

This data sheet contains basic information about our products. Its contents have been compiled with the utmost care and are continually updated. We therefore reserve the right to make changes of any kind. Please do not hesitate to contact us personally for further information.

Version 09/2024

