

DATA SHEET

T-rocket for precast walls

Material:

RÜDE Steel (ST), Polypropylen (PP)

RÜDE PVC-, CFC- and HFC-free

Product information :

RÜDE Spacer for double wall production of 8/10 mm steel with injection-moulded head and foot. By the injection of head and foot, we reach minimal differences in the length of individual rockets which guarantee accurate walls during concreting.

RÜDE Concrete cover of 15, 20, 25 and 30 mm with 8 mm steel for lengths up to 300 mm. Concrete cover of 35, 40, 45 und 50 mm with 10 mm steel for lengths up to 300 mm.

RÜDE The T-rockets can be extended using our attachment pieces in 10, 20, 30 and 40 mm lengths. The attachment pieces do not fit the mounted T-rockets.

RÜDE Packaging units and dimensions available:

ITEM NUMBER	HEIGHT Dimension in mm	STEEL Dimension in mm	BAG PU in piece	PALLET PU in piece
364.t8150	* 150	8	100	5.000
364.t8180	180	8	100	5.000
364.t8200	200	8	100	5.000
364.t8240	240	8	100	4.000
364.t8250	250	8	100	4.000
364.t8300	300	8	50	3.000
364.t10300	300	10	50	2.000
364.t10320	* 320	10	50	2.000
364.t10350	350	10	50	1.500
364.t10360	* 360	10	50	1.500
364.t10365	365	10	50	1.500
364.t10400	400	10	50	1.500
364.t10450	* 450	10	50	1.500
364.t10500	* 500	10	50	1.500

* mounted version

Note:

This data sheet contains basic information about our products. Its contents have been compiled with the utmost care and are continually updated. We therefore reserve the right to make changes of any kind. Please do not hesitate to contact us personally for further information.

